







ORTUS S.A.
 Address: Block B, unit 17-09 Megan avenue
 Jalan Yap Kwan Seng 12
 Kuala Lumpur, Malaysia 50450
 Email: info@ortusindustries.com

Off-Line Printing Machine

	 OR-E1-D	 OR-E2-D	 OR-E4-D	 OR-E6-D
MODEL OF MACHINE	LPM-E1-60A, LPM-E1-80A LPM-E1-100A, LPM-E1-120A LPM-E1-150A	LPM-E2-60, LPM-E2-80 LPM-E2-100, LPM-E2-120 LPM-E2-150	LPM-E4-60, LPM-E4-80 LPM-E4-100, LPM-E4-120 LPM-E4-150	LPM-E6-60, LPM-E6-80 LPM-E6-100, LPM-E6-120 LPM-E6-150
PRINTING COLOR	1-COLOR	2-COLOR	4-COLOR	6-COLOR
PRINTING POSSIBILITY	1+0	2+0, 1+1	4+0, 3+1, 2+2	6+0, 5+1, 4+2, 3+3
PRINTING WIDTH	600 mm / 800 mm / 1000 mm / 1200 mm / 1500 mm			
PRINTING LENGTH	S TYPE : 10" – 35" ; E TYPE : 9" – 40"			
PRINTING SPEED	Stack type: Max. 80 M/min (Single Face); Max. 60 M/Min (Double Face) Doctor Blade type: Max. 120 M/Min (Single Face); Max. 100 M/Min (Double Face)			
PRINTING CYLINDER	STANDARD 20" (508 mm) or To be Specified by Buyer			
ANILOX ROLLER	250 PLI (Stack type : Hard Chrome plated ; Doctor Blade Type : Ceramic)			
CYLINDER UP/DOWN	PNEUMATIC SYSTEM			
COLOR REGISTRATION	BY PUSH BUTTON			
DRYING SYSTEM	HOT AIR BOX			
UNWIND & REWIND	1-STATION UNWIND & 1-STATION REWIND			
OPTIONS	Ink Pump, Additional Printing Cylinders, Doctor Blade, Auto Tension Control, EPC Double Unwind & Double Rewind, Hydraulic System for Cylinder Up/Down and etc.			